






电性参数

Electrical Parameters

Parameter	Symbol	Rating		Unit
Consumed power	Pd	R	50	mW
		B	70	
Peak Forward current	IFP	R	80	mA
		B	80	
Forward working current	IF	R	20	mA
		B	20	
Reverse voltage	VR	R	5	V
		B	5	
Antistatic ability				
Operating ambient temperature	Topr		-40	


典型特性曲线

Typical Characteristics Curves




















使用注意事项 (3)

Precautions (3)

4. 其他事项

Others

When handling the product, touching the encapsulant with bare hands will not only contaminate its surface, but also affect on its optical characteristics. Excessive force to the encapsulant might result in catastrophic failure of the LEDs due to die breakage or wire deformation. For this reason, please do not put excessive stress on LEDs, especially when the LEDs are heated such as during Reflow Soldering.



LED

The epoxy resin of encapsulant is fragile, so please avoid scratch or friction over the epoxy resin surface. While handling the product with tweezers, do not hold by the epoxy resin, be careful.

5. 眼睛保护忠告

Safety Advice For Human Eyes

LED

LED

Viewing direct to the light emitting center of the LEDs, especially those of great Luminous Intensity, will cause great hazard to human eyes. Please be careful.

If there are any modifications to the specification sheet, no further notice will be given