

XL-PD438B

技术数据表 Technical Data Sheet

特点 (characteristic) :

- * L/W/H :6.6*4.8*3.8 mm
- Outline Dimensions (L / w / h): 6.6x 4.8 x 3.8mm
- * : /

Luminous color and colloid: infrared receiver tube black colloid

- * ROHS
- Environmental protection products Complied With ROHS Directive
- * MSL :3
- Moisture sensitivity level MSL : 3 levels
- * EIA
- EIA standard packaging

*

High energy efficiency, fast startup



应用领域 (product application) :

*

Medical equipment

*

Infrared remote controller

*

Camera monitoring head

*

Industrial control: counters, thermal imaging, smart meter

*


Infrared photoelectric switch

*

Wireless communication and signal transmission

*

Intelligent car, robot



目录

Contents


Electrical Characteristics.....3

Typical Characteristic Curves.....5

Outline Dimensions.....6

Packaging.....7


Precautions.....9



电性参数

Electrical Characteristics


Parameter	Symbol	Maximum rating	Unit
Power consumption	Pd	150	mW
Reverse Voltage	VR	32	V
Operating ambient temperature	Topr	-40°C ~ +85°C	
Storage ambient temperature	Tstg	-40°C ~ +85°C	
Welding conditions	Tsol	260 ≤ 6S	



Initial Electrical Optical Characteristics Ta=25

Parameter	Symbol	Min	Represe ntative	Max	Unit	Condition
Open-Circuit Voltage	VOC	/	0.35	/	V	$\lambda = 940\text{nm}$ $E_e = 1\text{mW/cm}^2$
Short-Circuit Current	Isc	/	18	/	μA	$\lambda = 940\text{nm}$ $E_e = 1\text{mW/cm}^2$
Reverse Light Currente	IL	15	25	/	μA	$\lambda = 940\text{nm}$ $V_R = 5\text{V}$ $E_e = 1\text{mW/cm}^2$
Reverse Dark Current	ID	/	5	30		





||



40V


典型特性曲线

Typical Characteristics Curves



外形尺寸

Outline Dimension



(Note)


1. Dimensions are in millimeters
2. $\pm 0.30\text{mm}$
Tolerances unless mentioned are $\pm 0.30\text{mm}$





包装

Packaging

Moisture Proof and Antti-Electrostatic Foil Bag




Label Expansion







使用注意事項 (2)



使用注意事項 (3)

