

目录

Catalogue

电性参数

Max Continuous Forward Current	IF		

Luminous Intensity	Iv	50	200	300	mcd	IF=20mA
Dominant Wave Length	λd	585	/	595	nm	IF=20mA
Peak Wave Length	λp	/	590	/	nm	IF=20mA
Forward Voltage	VF	1.8	2.2	2.4	V	IF=20mA
Viewing Angle	2Ø1/2	/	110	/	deg	IF=20mA
Spectral Width at half height	λ	/	20	/	nm	IF=20mA
Reverse Current	IR	/	/	≤10	μA	VR=5V

±10% ±0.1V (X,Y) ±0.01 ±1nm

Note: the light intensity error is 10%; The pressure drop error is ±0.1V ; (X,Y) coordinate deviation ±0.01 wavelength error ±1 nm.

亮度分档

：

代码	最小值	最大值	单位	测试条件

电压分档

：

代码	最小值	最大值	单位	测试条件

波长分档

典型特性曲线



正向电流降额曲线
Forward current derating curve



相对光强与正向电流特性
Relative Luminous VS Forward Current

光强与环境温度曲线
Luminous Intensity VS Ambient Temperature



相对辐射强度与空间角度关系
Radiation diagram

±

±

可靠性试验

Reliability Test Items And Conditions

Endurance test	Working life	Ta=25 ±5 ,IF=20mA	1000hrs	22 PCS	0/1
	High temperature and high humidity experiment	Ta= 85±5 , RH= 85 90%	1000hrs	22 PCS	0/1
	High-temperature storage	Ta= 85±5	1000hrs	22 PCS	0/1
	Low temperature storage	Ta= -40±5	1000hrs	22 PCS	0/1
Environmental testing	Cold and hot cycle	100 ±5 30mins 5mins -40 ±5 30mins	100 Circles	22 PCS	0/1
	Hot and cold impact	105 ±5 5mins -45 ±5 5mins	100 Circles	22 PCS	0/1
Mechanical Test	Resistance to Soldering Heat	T.sol= 250 ± 5	2times	22 PCS	0/1
	Lead Integrity	Load 2.5N(0.25kgf) 0°~ 90° ~0°	3times	22 PCS	0/1

外形尺寸

1.

2. mm .

使用注意事項（ ）

LED

LED 3

使用注意事项（ ）

LED

LED