

XL-IRM0038C

技术数据表 Technical Data Sheet



PIN
IC,
REACH ROHS





This product contains a high-speed and high sensitivity pin photo diode and Low power consumption, high gain Preamplifier Ic Adopting epoxy resin plastic encapsulated semi circular spherical packaging Dual shielding and anti-interference design for both inside and outside,This product has been certified by Reach and Rohs as an environmentally friendly product, Used as a receiver in infrared remote control systems

特点 (characteristic) :

Small volume epoxy resin plastic sealing patch packaging
* * * : 4.5*4.0*2.3*3.1mm
Appearance dimension length * width * height* foot length : 4.5*4.0*2.3*3.1mm

应用领域 (product application) :



目录

Catalogue

电性参数
Electrical Characteristics.....3

典型特性曲线
Typical Characteristic Curves.....7

可靠性实验
Reliability Test Items And Conditions.....8

外形尺寸
Outline Dimensions.....9

包装
Packaging.....10

使用注意事项
Precautions.....11

电性参数

Electrical Characteristics

Absolute Maximum Ratings Ta=25


Parameter	Symbol	Rating	Unit
			6


Initial Electrical Optical Characteristics Ta=25

Parameter	Symbol		Min.	Typ.	Max.	Unit	Test conditions
	ICC		0.3	0.4	0.5	mA	VDD=5V
	L	0 °	15	20	-	M	/
	L	35 °	5	7	-	M	
	L	35 °	5	7	-	M	
	f _o		-	37.9	-	KHZ	/
BPF	f _{BW}		-	6	-	KHZ	/
	V _{oI}		-	-	250	mV	I _{sink} =2.0mA
	V _{oh}		4.5	-	5.0	V	VCC=5V
	T _{pwl}		400	600	800	us	burst wave Vin=500UVp-p
	T _{PWH}		400	640	800	us	burst wave Vin=50mVp-p
	T _{burst}		350	-	-	us	Vin=50mVp-p
	T _{burst gap}		450	-	-	us	Vin=50mVp-p
	T _{pause}		45	-	-	us	Vin=50mVp-p



Parameter	Symbol	Min.	Typ	Max.	Unit
	VDD	2.7	-	5.5	V





接收距离分档:
Receive distance grading


代码 Code	最小值 Min	最大值 Max	单位 Unit	测试条件 Test conditions

工作电压分档:
Working voltage grading

代码 Code	最小值 Min	最大值 Max	单位 Unit	测试条件 Test conditions

工作电流分档:
Working current grading

代码 Code	最小值 Min	最大值 Max	单位 Unit	测试条件 Test conditions



典型特性曲线

Typical Characteristics Curves

Test waveform




Figure 4. Typical Bandpass Curve





Figure 4. Supply Current vs supply voltage




可靠性试验

Reliability Test Items And Conditions


* Reliability Test Project

	260 ± 5	5	20	20
	100PF 1.5KΩ , 4KV ,		20	20
	10-50HZ/1min 1.5mm X Y Z/30min	30	20	20
	85 ± 2	240	20	20
	-20 ± 2	240	20	20



外形尺寸

Outline Dimension




- 1.
2. mm .

包装(1)

Packaging(1)

2.


圆盘及载带卷出方向及空穴规格 Disk and carrier belt direction of roll and hole dimensions




包装 (2)

Packaging (2)

防潮防静电包装 Moisture Proof and Anti-Static Foil Bag



外包装箱 Carboard Box



标签说明 Label Expantion



焊接指南 (1)

Guideline for Soldering (1)


使用烙铁手工焊接

Hand Soldering

30

2. 回流焊接:

Reflow Soldering:



焊接指导 (2)

Guideline for Soldering (2)

3. Cleaning

Cleaning

* 注意:

PCB

⚠ Note:

使用注意事項 (1)

Precautions (1)

貯蔵

Storage

168 7

4

n n

140


2

使用注意事项 (3)

Precautions (3)

3. 其他事项:

Others



4. 眼睛保护忠告:

Safety Advice For Human Eyes