

XL-504UBC

F5

光亮度高

特点 () :

* : F5/5.5*5.0*8.7*28mm

Appearance dimension: F5/5.5*5.0*8.7*28mm

* : /

Luminous color and colloid: blue brightness White /water colloid

* ROHS

Environmental protection products meet ROHS requirements

* MSL :2

Moisture sensitivity level MSL : 2 levels

* EIA

EIA standard packaging

*

Long operating life

*

High energy efficiency, fast startup

*

Low voltage DC drive

应用领域 () :

* ;

Home appliances, digital, communication

*

Automotive Electronics

*

Lighting decoration

*

electronic toy

*

electronic clock

*

Traffic instructions

*


Medical beauty instruments

*

Electronic teaching equipment

*

Urban lighting



自性参数

Consumed power	Pd	70	mW
Max Continuous Forward Current	IF	20	mA
Peak Forward Current	IFp	80	mA
Operating ambient temperature	Topr	-20 ° C ~ +85 ° C	
Storage ambient temperature	Tstg	-40 ° C ~ +85 ° C	
Welding conditions	Tsol	reflow soldering 240 ° C 6s manual welding 300 ° C 3s 2.0mm	

Luminous Intensity	Iv	3000	4500	6000	mcd	IF=20mA
Dominant Wave Length	λ d	460	465	475	nm	IF=20mA
Peak Wave Length	λ p	/	465	/	nm	IF=20mA
Forward Voltage	VF	2.8	3.0	3.4	V	IF=20mA
Viewing Angle	2θ1/2	/	30	/	deg	IF=20mA
Spectral Width at half height	λ	/	30	/	nm	IF=20mA
Reverse Current	IR	/	/	≤ 10	μ A	VR=5V


± 10%

± 0.1V (X,Y)

± 0.01

± 1nm

Note: the light intensity error is 10%; The pressure drop error is ±0.1V ; (X,Y) coordinate deviation ±0.01 wavelength error ±1 nm.



亮度分档

:

代码	最小值	最大值	单位	测试条件


电压分档

:



代码	最小值	最大值	单位	测试条件


波长分档

代码	最小值	最大值	单位	测试条件
----	-----	-----	----	------




典型特性曲线






外形尺寸




- 1.
- 2. mm .






使用注意事項 ()

LED





使用注意事項

8、其他事項：

*

*