XL-234SYGD-L　　234绿发普绿长脚　　技术数据表

特点（　　）：

*　　:3.0*2.0*4.0*28mm

Appearance dimension: 3.0*2.0*4.0*28mm

*　　:　　/

Luminous color and colloid: yellow green brightness White /green colloid

*　　ROHS

Environmental protection products meet ROHS requirements

*　　MSL　:2

Moisture sensitivity level　MSL　: 2levels

* EIA

EIA standard packaging

*

目录

Catalogue

[redacted]

电性参数

Max Continuous Forward Current	IF		

Luminous Intensity	Iv	50	/	100	mcd	IF=20mA
Dominant Wave Length	λd	565	/	575	nm	IF=20mA
Peak Wave Length	λp	/	570	/	nm	IF=20mA
Forward Voltage	VF	2.0	2.4	2.6	V	IF=20mA
Viewing Angle	2Ø1/2	/	110	/	deg	IF=20mA
Spectral Width at half height	λ	/	15	/	nm	D

亮度分档

：

代码	最小值	最大值	单位	测试条件

电压分档

：

代码	最小值	最大值	单位	测试条件

波长分档

典型特性曲线

光谱分布曲线



伏安特性

正向电流降额曲线



相对光强与正向电流特性
Relative Luminous VS Forward Current

光强与环境温度曲线
Luminous Intensity VS Ambient Temperature



相对辐射强度与空间角度关系
Radiation diagram



±

±

可靠性试验

Reliability Test Items And Conditions

Endurance test	Working life	Ta=25 ±5 ,IF=20mA	1000hrs	22 PCS	0/1
	High temperature and high humidity experiment	Ta= 85±5 , RH= 85 90%	1000hrs	22 PCS	0/1
	High-temperature storage	Ta= 85±5	1000hrs	22 PCS	0/1
	Low temperature storage	Ta= -40±5	1000hrs	22 PCS	0/1
Environmental testing	Cold and hot cycle	100 ±5 30mins 5mins -40 ±5 30mins	100 Circles	22 PCS	0/1
	Hot and cold impact	105 ±5 5mins -45 ±5 5mins	100 Circles	22 PCS	0/1
Mechanical Test	Resistance to Soldering Heat	T.sol= 250 ± 5	2times	22 PCS	0/1
	Lead Integrity	Load 2.5N(0.25kgf) 0 ° ~ 90 ° ~0 °	3times	22 PCS	0/1

外形尺寸



1.

2. mm .

包装



使用注意事項（ ）

LED

使用注意事项（ ）

LED

LED





使用注意事项（ ）

8、其他事项：

*

*