

XL-2520SYGC/T

技术数据表 Technical Data Sheet

2520普绿光 直插小蝴蝶

特点 (characteristic) :

* Ø

c



自性参数

Electrical Characteristics

Absolute Maximum Ratings Ta=25


Parameter	Symbol	Value	Unit
Max Power Dissipation	PD	50	mW
Max Continuous Forward Current	IF	20	mA
Peak Forward Current	IFP	80	mA
Max Reverse Voltage	VR	5	V
Antistatic ability	ESD	2000	V
Operating Temperature Range	TOPR		°C
Storage Temperature Range	TSTR		°C

Initial Electrical Optical Characteristics Ta=25

Parameter	Symbol	Min.	Typ.	Max.	Unit	Test conditions
Luminous Intensity	Iv	50	/	200	mcd	IF=20mA
Dominant Wave Length	λd	565	/	575	nm	IF=20mA
Peak Wave Length	λp	/	570	/	nm	IF=20mA
Forward Voltage	VF	1.8	/	2.4	V	IF=20mA
Half wave width		/	15	/	nm	IF=20mA
Viewing Angle	2 1/2	/	20 °	/	deg	IF=20mA
Reverse Current	IR	/	/	≤5	μA	VR=5V









使用注意事項 (1)

Precautions (1)

1. 貯存:

Storage

!

山

!

Ń

山

Ń

!

Ń

SSS

