1 <250 :3s

Manual welding temperature:<250 ; Welding time: 3 seconds

2 100 120 ˆ1 235-245 <3s

Preheating temperature for tin immersion and wave soldering: 100 (not exceeding 120 , with stable heating), soldering temperature: 235-245 (search for optimal temperature), soldering time:<3s

3 ₮ ▲ ˆ1

Exceeding the above conditions leads to a sharp increase in digital tube failure

1 غ ˆ1 ĭ ˇ

When in use, the current and voltage must be correct; Add current limiting resistors to segments and decimal points;

2 ج ضي Ũ غ ضي ʅ ↕

.

The product should not be stored or used in corrosive gases, and should not be exposed to air for too long, otherwise it may cause oxidation;

3 ĭ كح ضر

All devices and instruments that come into contact with digital devices must be grounded

4 ج ˆ ضي ╟

Products with protective film on the surface can be peeled off before use

5 U

After removing the protective film, do not touch the surface of the digital tube with your hands

6 ˆ1 ŭ ω̈ ŭ ω̈ ═

Voltage used: segment: according to the color of the light emission; Decimal point: determined by the glowing color

7 ˉ شخ 4-5mA 100mA

Current usage: Dynamic average current 4-5mA, peak current 100mA

8 ضي ŭ

Please take anti-static measures when using blue, emerald green, and white digital tubes

9 ˆ1 ₮ شخ

Recommended for constant current use, as constant voltage may cause uneven brightness