Part No. :XL-

规格数据表

ta Sh

ristic)

11.3*15.0*10.3mm

sion: F 11.3*15.0*10.3mm

: /

目录
Catalogue

Electrical Characteristics.....3

Typical Characteristic Curves.....5

Outline Dimensions.....7

Packaging..... 8

Precautions..... 9

电性参数

Electrical Characteristics

Absolute Maximum Ratings Ta=25

Parameter	Symbol	Rating	Unit
Consumed power	Pd	70	mW
Max Continuous Forward Current	IF	20	mA

亮度分档:
Brightness grading:

代码 Code	最小值 Min	最大值 Max

电压分档:
Voltage grading:

色温分档:
Color temperature grading

典型特性曲线

Typical Characteristics Curves







: 25 + 5 C./Note: If not otherwise indicated, the test environment temperature is 25 + 5 C.

可靠性试验项目及条件

Reliability Test Items And Condition

Class	Test item	Testing environment	Testing time	Qty	Fail qty
	Working Life	Ta=25 ℃ ,IF=20mA	1000hrs	22 PCS	0/1

[redacted]

外形尺寸

Outline Dimension



(Note)

1. Dimensions are in millimeters.

2. Tolerances unless mentioned are ± 0.25mm.

使用注意事项（1）

Precautions (1)

1. **APPLY**

LED LED

This LED can be used in some ordinary electronic equipment, such as office equipment, communication equipment, house decoration, if LED is used in some high reliability requirements, such as air transportation, traffic control and medical liao equipment, must refer to the information provided by sales.

2R Keeping in storage

LED 30 70% LED

Storage environment of LED with temperature not exceeding 30 and relative humidity not exceeding 70%.It is recommended that LDE be used in the original

使[redacted]意事项(2)

P[redacted]

使用注意事项（3）

P[redacted]/(3)

8、其他事项：

Others

*

*When handling the product, touching the encapsulant with bare hands will not only contaminate its surface, but also affect on its optical characteristics. Excessive force to the encapsulant might result in catastrophic failure of the LEDs due to die breakage or wire deformation. For this reason, please do not put excessive stress on LEDs, especially when the LEDs are heated such as during Reflow Soldering.



*LED

*The epoxy resin of encapsulant is fragile, so please avoid scratch