


DIP6

SMD6



- Current transfer ratio
(CTR: 50 - 500% at $I_F = 10\text{mA}$, $V_{CE} = 10\text{V}$)
 - High isolation voltage between input and output ($V_{iso} = 5000\text{Vrms}$)
 - Operating Temperature: $-55 \sim 100$
 - Environmentally friendly products, compliant with CQC, UL, and VDE requirements
-
- Case: DIP6, SMD6
 - Molding Compound: UL Flammability Classification Rating 94V-0
 - Terminals: Matte tin-plated leads; solder ability-per MIL-STD-202, Method 208
-
- It is widely used in the feedback control loops of switching power supplies and the isolation between main circuits and control circuits, ensuring stable output voltage and quickly transmitting fault signals to trigger protection mechanisms in the event of overload or short circuit.
 - Photovoltaic energy storage system
 - Data collection, inverter control, protection circuit
 - Industrial automation control
 - Relay drive, motor control, PLC interface
 - Power management
 - Switching power supply feedback isolation Home appliance power control















he

- XINGLIGHT implements dynamic technical updates. Specifications are subject to change. Refer to the official website for the latest version.
- Users must strictly adhere to specified conditions. Failures caused by misuse (overload, high temperature, incompatible circuits) are excluded from warranty.
- Contact technical support for details.

selection